


RISER QUANTITY / M²



Jouplast®



www.jouplast.com

TERRACE AND PATIOS		AREA						
TILE / PAVEMENT SIZE	INSTALLATION TYPE	20 m ²	40 m ²	60 m ²	80 m ²	100 m ²	200 m ²	1 000 m ²
40 x 40 cm	1 riser pedestal / corner	7.8	7.2	6.9	6.8	6.8	6.6	6.5
45 x 45 cm	1 riser pedestal / corner	6.4	6	6	5.7	5.7	5.5	5.2
50 x 50 cm	1 riser pedestal / corner	5	4.7	4.6	4.5	4.4	4.3	4.1
60 x 60 cm	1 riser pedestal / corner	4	3.6	3.3	3.2	3.2	3.1	2.9
75 x 75 cm	1 riser pedestal / corner + 1 / slab side	7.8	7.2	6.8	6.5	6.3	6	5.7
80 x 80 cm	1 riser pedestal / corner + 1 / slab side	7.5	7	6.4	6.1	5.8	5.6	5.2
50 x 80 cm	1 riser pedestal / corner + 1 / larger slab side	6.3	6	6	5.7	5.5	5.5	5.3
90 x 90 cm	1 riser pedestal / corner + 1 / slab side	6.2	5.7	5.2	5	4.8	4.4	4.2
30 x 90 cm	1 riser pedestal / corner + 1 plot / larger slab side	9.8	9.6	9.3	9	8.8	8.3	7.8
45 x 90 cm	1 riser pedestal / corner + 1 / larger slab side	6.8	6.5	6.2	6	5.8	5.6	5.2
60 x 90 cm	1 riser pedestal / corner + 1 / larger slab side	5.3	5.1	4.8	4.4	4.3	4.1	3.9
100 x 100 cm *	1 riser pedestal / corner + 1 / slab side	4.9	4.6	4.4	4	3.8	3.6	3.2
50 x 100 cm *	1 riser pedestal / corner + 1 larger slab side	5	4.7	4.6	4.5	4.4	4.3	4.1
20 x 120 cm **	1 riser pedestal / corner + 1 / larger slab side	11,3	9,2	8,6	8,6	8,6	8,3	7,9
30 x 120 cm *	1 riser pedestal / corner + 1 / larger slab side	7.5	6.8	6.3	6.3	6.3	6.1	5.8
40 x 120 cm *	1 riser pedestal / corner + 1 / larger slab side	6.3	5.8	5.4	5.2	4.9	4.7	4.5
60 x 120 cm *	1 riser pedestal / corner + 1 / larger slab side	4	3.6	3.3	3.2	3.2	3.1	2.9
120 x 120 cm *	1 riser pedestal / corner + 1 / slab side	3.6	3.4	3.1	2.8	2.8	2.6	2.3

* For these sizes, we recommend to use PROFILDECK®, our aluminium sub-frame system. Feel free to contact us regarding quantities

** Can only be laid on paving riser pedestals with a height greater than 40 mm. For lower heights, laying on paving riser pedestals is not compatible, use Profildeck®.


- Consult with paving manufacturer to ensure compatibility with riser system and to check quantity - Please make sure that you use 32 mm (min) pressed/self-supporting concrete slabs or 20 mm thick (min) Ceramic/Porcelain paving. (T7, T11 or F+ standard).

LATERAL FINISHING

For a 60 x 60 cm square tile :

- against the wall : one side finishing plate per slab plus 1 more. Example : 6 tiles against the wall, 7 side finishing plates are needed.
- along the terrace : one side finishing plate per slab plus 1 more, the same for the lateral riser support. Example : for 6 tiles along the terrace, 7 side finishing plates and 7 lateral riser supports are needed.

- This document is to be considered as guidance only, it is not a contractual commitment.

RISER QUANTITY / M²

Jouplast®



www.jouplast.com

DECKING		AREA						
Decking board type	INSTALLATION TYPE	20 m ²	40 m ²	60 m ²	80 m ²	100 m ²	200 m ²	1 000 m ²
WOOD	Distance between decking joists : 50 cm 1 riser pedestal / 70 cm under decking joist	4.1	3.9	3.7	3.5	3.4	3.2	3
	Distance between decking joists : 50 cm 1 riser pedestal / 70 cm under decking joist	5	4.7	4.6	4.5	4.4	4.3	4.1
COMPOSITE	Distance between decking joists : 40 cm 1 riser pedestal / 70 cm under decking joist	4.6	4.6	4.4	4.2	4.1	3.9	3.8
	Distance between decking joists : 40 cm 1 riser pedestal / 70 cm under decking joist	6.1	5.8	5.6	5.5	5.5	5.3	5.2

- Decking joist must be made of wood or metal, NOT COMPOSITE.

• This document is to be considered as guidance only, it is not a contractual commitment.